



Sirius Interactive Flat Panel Display from Galtech

Enjoy seamless collaboration in classrooms and business meetings



Education



Trainings



Boardroom meetings



Conferences

Sirius Interactive Flat Panel Display

Sirius Interactive Flat Panel Display from Galtech is designed to integrate projector, whiteboard, audio, monitor, computer, microphone, camera and multimedia interactive terminals. Multiple functions like writing, annotation and wireless screen sharing are user-friendly and add convenience in digital education and intelligent conferencing.



A rich experience through a wide range of features

Screen size: 65" | 75" | 86" | 98"



4K resolution



4mm protect glass/
anti-scratch



450 nits brightness



16.7million colour



4GB RAM/
32GB memory



Android 11/12/13 OS



Infrared touch
technology



20 point touch



60,000 hrs Life



MoHS 8 grade
tempered glass



Anti-glare screen



Password/pattern
lock protected



40 watts speaker



Premium
aluminium body



Wireless
screen sharing

Sirius Interactive Flat Panel Display comes in screen sizes of 65"/75"/86"/98" to suit your specific requirement.

Technical specifications for quick comparison

Model	65 Inches	75 Inches	86 Inches	98 Inches
Product model	Sirius 65 GE	Sirius 75 GE	Sirius 86 GE	Sirius 98 GE
Display Parameter	ADS Zero bonding touch 1428.48(H) x 803.52(V) Display Ratio 16:9 Brightness ≥450cd/m ² Contrast Ratio 1200:1 Response time 6-8ms Backlight Type DLED Viewing Angle 178°(V)/178°(H) Resolution 3840(H) X 2160(V) Speaker 20W*2, Soundtrack 2.0	ADS Zero bonding touch 1649.66(H) x 927.97(V) 16:9 ≥450cd/m ² 1200:1 6-8ms DLED 178°(V)/178°(H) 3840(H) X 2160(V) 20W*2, Soundtrack 2.0	ADS Zero bonding touch 1897(H) x1068(V) 16:9 ≥450cd/m ² 1400:1 6-8ms DLED 178°(V)/178°(H) 3840(H) X 2160(V) 20W*2, Soundtrack 2.0	ADS Zero bonding touch 1897(H) x1068(V) 16:9 ≥450cd/m ² 1400:1 6-8ms DLED 178°(V)/178°(H) 3840(H) X 2160(V) 20W*2, Soundtrack 2.0
Android Specs	Amlogic T982 Quad Core A55*4 1.9GHz Mali G52MP2 Android 11.0 4 GB 32 GB	Amlogic T982 Quad Core A55*4 1.9GHz Mali G52MP2 Android 11.0 4 GB 32 GB	Amlogic T982 Quad Core A55*4 1.9GHz Mali G52MP2 Android 11.0 4 GB 32 GB	Amlogic T982 Quad Core A55*4 1.9GHz Mali G52MP2 Android 11.0 4 GB 32 GB
Wireless module	Version 5.0; frequency 2.4GHz; distance 0-10m Version 802.11ac/b/g/n/a/ax; frequency 2.4GHz/5GHz; distance 0-10m	Version 5.0; frequency 2.4GHz; distance 0-10m Version 802.11ac/b/g/n/a/ax; frequency 2.4GHz/5GHz; distance 0-10m	Version 5.0; frequency 2.4GHz; distance 0-10m Version 802.11ac/b/g/n/a/ax; frequency 2.4GHz/5GHz; distance 0-10m	Version 5.0; frequency 2.4GHz; distance 0-10m Version 802.11ac/b/g/n/a/ax; frequency 2.4GHz/5GHz; distance 0-10m
I/O Interface	HDMI IN 1 USB 2.0 1 USB 3.0 1 TOUCH USB 2.0 1 AUDIO IN 1 AUDIO OUT 1 COAXIAL OUTPUT 1 EARPHONE 1 RS232 1 RJ45 1	HDMI IN 1 USB 2.0 1 USB 3.0 1 TOUCH USB 2.0 1 AUDIO IN 1 AUDIO OUT 1 COAXIAL OUTPUT 1 EARPHONE 1 RS232 1 RJ45 1	HDMI IN 1 USB 2.0 1 USB 3.0 1 TOUCH USB 2.0 1 AUDIO IN 1 AUDIO OUT 1 COAXIAL OUTPUT 1 EARPHONE 1 RS232 1 RJ45 1	HDMI IN 1 USB 2.0 1 USB 3.0 1 TOUCH USB 2.0 1 AUDIO IN 1 AUDIO OUT 1 COAXIAL OUTPUT 1 EARPHONE 1 RS232 1 RJ45 1
OPS Computer (Spec.is optional)	Front small board interface 3*USB 3.0+TYPE-C+TOUCH OUT+HDMI IN Window CPU Intel i3/i5/i7 System Version Windows 10 Pro/11 Pro Internal Storage 4GB/8GB/16GB/32GB Hard Disk SSD 128/256/512 GB Graphics Integrated WIFI Yes	3*USB 3.0+TYPE-C+TOUCH OUT+HDMI IN Intel i3/i5/i7 Windows 10 Pro/11 Pro 4GB/8GB/16GB/32GB 128/256/512 GB Integrated Yes	3*USB 3.0+TYPE-C+TOUCH OUT+HDMI IN Intel i3/i5/i7 Windows 10 Pro/11 Pro 4GB/8GB/16GB/32GB 128/256/512 GB Integrated Yes	3*USB 3.0+TYPE-C+TOUCH OUT+HDMI IN Intel i3/i5/i7 Windows 10 Pro/11 Pro 4GB/8GB/16GB/32GB 128/256/512 GB Integrated Yes
Others	PC Interface *VGA*,HDMI*,WIFI*,LAN*,COM*, MIC-IN*,LINE-OUT*, USB2.0*5,USB3.0*1 Power Dissipation ≤180W Standby consumption ≤0.5W power supply 100-240V-50/60Hz 4A Full Dimension 1485.14(L)*887.34(H) *88.69 (D)mm VESA hole specification 500(L)*400(W)mm Wall mounting screw spec. M8*25mm Packing way Carton Net Weight 38kg Gross Weight 49kg Package size 1621(L)*1052(H)*220(D)mm Touch technology Non-contact Infrared sensing technology Touch type 20 point touch Min. Identifier ±2mm Resolution of touch screen 32767(W)*32767(D) Touch depth ±1mm Response time ≤4ms Drive Mode USB Drive Free Writing surface material 4mm Anti-glare tempered glass with 8 MOHS Touch Screen Sensor Mode Opaque object (finger, writing pen etc.)	*VGA*,HDMI*,WIFI*,LAN*,COM*, MIC-IN*,LINE-OUT*, USB2.0*5,USB3.0*1 ≤280W ≤0.5W 100-240V-50/60Hz 4A 1706.23(L)*1012.49(H) *88.5(D)mm 600(L)*400(W)mm M8*25mm Carton 55kg 68kg 1841(L)*1175(H)*220(D)mm Non-contact Infrared sensing technology 20 point touch ±2mm 32767(W)*32767(D) ±1mm ≤4ms USB drive free 4mm Anti-glare tempered glass with 8 MOHS Opaque object (finger, writing pen etc.)	*VGA*,HDMI*,WIFI*,LAN*,COM*, MIC-IN*,LINE-OUT*, USB2.0*5,USB3.0*1 ≤440W ≤0.5W 100-240V-50/60Hz 4A 1953.5(L)*1152.4(H) *86.6(D)mm 800(L)*400(W)mm M8*25mm Carton 70kg 87kg 2088(L)*1315(H)*220(D)mm Non-contact Infrared sensing technology 20 point touch ±2mm 32767(W)*32767(D) ±1mm ≤4ms USB drive free 4mm Anti-glare tempered glass with 8 MOHS Opaque object (finger, writing pen etc.)	*VGA*,HDMI*,WIFI*,LAN*,COM*, MIC-IN*,LINE-OUT*, USB2.0*5,USB3.0*1 ≤440W ≤0.5W 100-240V-50/60Hz 4A 2088(L)*1315(H)*220(D)mm Non-contact Infrared sensing technology 20 point touch ±2mm 32767(W)*32767(D) ±1mm ≤4ms USB drive free 4mm Anti-glare tempered glass with 8 MOHS Opaque object (finger, writing pen etc.)
Accessories	Writing height ≤3mm Bonding Zero Bonding Writing display Double Stylus pen two-color Wall bracket 1 pc Touch Pen 2 pcs + Remote -1 Pc Power cable 1 pc (1.5M) Operation manual 1pc	≤3mm Zero Bonding Double Stylus pen two-color 1 pc 2 pcs + Remote -1 Pc 1 pc (1.5M) 1pc	≤3mm Zero Bonding Double Stylus pen two-color 1 pc 2 pcs + Remote -1 Pc 1 pc (1.5M) 1pc	≤3mm Zero Bonding Double Stylus pen two-color 1 pc 2 pcs + Remote -1 Pc 1 pc (1.5M) 1pc
Environmental Parameters	Working temperature 0-40 °C Working humidity 10%RH -90%RH Storage temperature -20-+60 °C Storage humidity 10%RH -90%RH Working life-time ≥60000hrs	0-40 °C 10%RH -90%RH -20-+60 °C 10%RH -90%RH ≥60000hrs	0-40 °C 10%RH -90%RH -20-+60 °C 10%RH -90%RH ≥60000hrs	0-40 °C 10%RH -90%RH -20-+60 °C 10%RH -90%RH ≥60000hrs

Galtech is a one stop solution provider for all office automation requirements. We help businesses realise the promise of technology by delivering a full spectrum of global technology and supply chain services to businesses across India. Expertise in technology solutions, mobility and supply chain solutions enables our business partners to operate efficiently and successfully in the markets they serve. Unrivalled agility, deep market insights and the trust and dependability that come from decades of proven relationships has made us a preferred choice.

Sirius Interactive Flat Panel Displays are designed in our world-class manufacturing facility in Bangalore to provide seamless collaboration in classrooms and business meetings



GALTECH®

Galtech InfoSolutions Pvt.Ltd

📍 No.50, 9th A Main Road, Indira Nagar 1st Stage,
Bengaluru Karnataka 560038

☎ +91 80 4852 9245

✉ marketing@galtechinfo.com

🌐 www.galtechinfo.com

Authorised Dealer